



DATE	REV.	REVISION	DRAFTING	CHECKED	APPROVED
2011.04.12	A/0	NEW	LUMIAO	ZXL	LANDER

WHITE INK MARKING:USB 3.0 Cable 28AWGx3P+28AWGx2C E139315-F5 AWM 2725 80°C 30V VW-1

SECTION A-A

Customer's P/N	Length	Description
SB 3022	0.5M	USB 3.0 A Male-Micro A Male
SB 3023	1M	USB 3.0 A Male-Micro A Male
SB 3024	1.5M	USB 3.0 A Male-Micro A Male
SB 3025	2M	USB 3.0 A Male-Micro A Male

Length(M)	Tolerances(M)
0.5	±0.015
1	±0.015
1.5	±0.02
2	±0.02

Unless specified on the drawing, tolerances are per the follows :

X. ± 0.20  
.X ± 0.10  
.XX ± 0.05

1	Terminal:Phos/Brass,G/F	USB 3.0 Micro A Male Plug	5
1	PVC: BLACK	Molding_Micro A Male	4
1	USB 3.0 CABLE 3P*28AWG+2C*28AWG	USB 3.0 Cable 28AWG	3
1	PVC: BLACK	Molding_A Male	2
1	Terminal:Phos/Brass,G/F	USB3.0 A Male Plug	1
Q'ty	SPECIFICATION	ITEM	NO



DRAW. NO	DESC.	USB 3.0 A TYPE MALE TO MICRO USB 3.0 A TYPE MALE			
DEPARTMENT	RD	DRAW	LUMIAO	DATE	2011.04.12
SCALE	N/A	CHECKED	ZXL	DATE	2011.04.12
UNIT	mm	APPROVED	LANDER	DATE	2011.04.12
		SHEET	1 OF 1		